

Specification

Product name: Flexible Split Loom

Material: PP

Working temperature: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$



- ☆Flammability: Self-extinguishing per FMV SS302
 - ☆Heat aging: No embrittlement and chalking after test at 125°C for 240h per QC/T29106
 - ☆Low temperature impact: A hammer of 300g free falls to impact the sample from 100mm, no signs of crack and breakage after test at -40°C for 4h per QC/T29106
- Color: Black. Other colors can be customized
- Application: Widely used in the protection of automotive low voltage wiring harness.
- Certificate: RoHS

Version	Modification content	Reviser	Date
A2	Revised table, added symbols ☆ of characteristics		20/3/2019

Part no.	Part no.	I.D. (ID) (mm)	O.D. (OD) (mm)	Wall thickness (T) (mm)	Packaging (Ft /roll)
SL-014P	1/4"	5.5 ± 0.3	8.5 ± 0.3	0.25 ± 0.05	10 or 50 FT
SL-038P	3/8"	10.0 ± 0.3	13.0 ± 0.3	0.30 ± 0.05	10 or 50 FT
SL-012P	1/2"	12 ± 0.4	15.8 ± 0.4	0.30 ± 0.05	10 or 50 FT
SL-034P	3/4"	17.0 ± 0.4	21.2 ± 0.4	0.32 ± 0.05	10 or 50 FT
SL-100P	1"	23.0 ± 0.4	28.5 ± 0.4	0.35 ± 0.05	10 or 50 FT

SL-xxxP-yy-zzz

xxx: yy: zzz:
 014 - 1/4" BK - Black 010 - 10 Ft
 038 - 3/8" NL - Natural 050 - 50 Ft
 012 - 1/2"
 034 - 3/4"
 100 - 1"

Manufacturer			
Specification No.		Unit	mm
Product code	SL-xxxP-yy-zzz	Version	A2
REV.0		Special characteristics	☆ Represent key special characteristics
Prepared		Date	20/3/2019
Checked		Date	20/3/2019
Approved		Date	20/3/2019